
CR-003 - 4-conductor through terminal block

Spare Part Number: CR-003

Net Weight: 7.60g

Net Dimensions: 5.20mm x 6.99mm x 3.29mm

Description

CR-003 4-conductor through terminal block

2.5 mm²; suitable for Ex e II applications; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm²; gray

WAG20021401

Specifications

Ratings per IEC/EN

Ratings per	IEC/EN 60947-7-1
Nominal voltage (III/3)	800V
Rated impulse voltage (III/3)	8kV
Rated current	24A
Rated current 2	32A
Legend (ratings)	(III / 3) ? Overvoltage category III / Pollution degree

Ratings per UL

Approvals per	UL 1059
Rated voltage UL (Use Group B)	600V
Rated current UL (Use Group B)	20A
Rated voltage UL (Use Group C)	600V
Rated current UL (Use Group C)	20A

Ratings per CSA

Approvals per	CSA 22.2 No 158
Rated voltage CSA (Use Group B)	600V
Rated current CSA (Use Group B)	20A
Rated voltage CSA (Use Group C)	600V
Rated current CSA (Use Group C)	20A

Equipment Ref

830 Ref **TB5, TB7**

812 Ref **TB2, TB3**

812 Ref **TB2, TB3**

Catalogues/Families

Spare Part Type

Electrical Component

Spare Part Group

Others	
Stock Type	
Made to Order	

Product Gallery